






VALVOLE SICUREZZA

SAFETY VALVES - VALVES DE SECURITE - VÁLVULAS DE SEGURIDAD

Temperatura max: 90°C – 195°F
 Max temperature: 90°C – 195°F
 Température maxi: 90°C – 195°F
 Temperatura máx: 90°C – 195°F

CODICE PART NR.	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Scarico By-pass	PESO WEIGHT		
		BAR	PSI	l/min	GPM			Kg	lbs	
 86.1670.00.2	VS 250	250	3600	24	6.3	3/8 BSP - F	3/8 BSP - F	0.36	0.8	
	86.1675.00.2	VS 250-2 BY-PASS 1/4	250	3600	24	6.3	N°2 3/8 BSP - F	1/4 BSP - F	0.46	1.0
	86.1660.00.2	VS 250-2 BY-PASS 3/8	250	3600	24	6.3	N°2 3/8 BSP - F	3/8 BSP - F	0.46	1.0
 86.1676.00.2	VS 350	350	5100	24	6.3	N°2 3/8 BSP - F	3/8 BSP - F	0.46	1.0	
 86.1677.00.2	VS 280 (AISI 303)	280	4000	80	21	N°2 1/2 BSP - F	1/2 BSP - F	1.21	2.7	
	86.1678.00.2	VS 400 (AISI 303)	400	5800	80	21	N°2 1/2 BSP - F	1/2 BSP - F	1.21	2.7
 86.1679.00.2	VS 500	500	7250	80	21	1/2 BSP - F	1/2 BSP - F	1.42	3.1	

ACCIAIO INOX
STAINLESS STEEL